

WHAT IS CLAIMED IS:

- sub
A1
1. An engine starter, comprising:
a recoil device;
5 a ring gear operatively rotated with said recoil device;
a recoil cover for accommodating said recoil device and said ring gear therein;
a starter device having pinions engaged with said ring
10 gear; and
a drain mechanism provided on said recoil cover for allowing a liquid entering from said recoil cover to be discharged by one-touch operation.
2. The engine starter according to claim 1, wherein
15 said drain mechanism includes a transparent pipe member attached to said recoil cover and a plug member fitted to said pipe member.
3. The engine starter according to claim 1, wherein
20 said recoil cover includes a window for allowing the liquid therein to be visible from outside.
4. The engine starter according to claim 2, wherein said recoil cover includes a window for allowing the liquid therein to be visible from outside.
5. The engine starter according to claim 1, wherein
25 said recoil cover includes a compressed air injection hole for introducing compressed air to forcibly discharge the liquid inside said recoil cover and a lid member for closing

said compressed air injection hole.

AI
cont 5 6. The engine starter according to claim 2, wherein
said recoil cover includes a compressed air injection hole
for introducing compressed air to forcibly discharge the
liquid inside said recoil cover and a lid member for closing
said compressed air injection hole.

10 7. The engine starter according to claim 3, wherein
said recoil cover includes a compressed air injection hole
for introducing compressed air to forcibly discharge the
liquid inside said recoil cover and a lid member for closing
said compressed air injection hole.

15 8. The engine starter according to claim 4, wherein
said recoil cover includes a compressed air injection hole
for introducing compressed air to forcibly discharge the
liquid inside said recoil cover and a lid member for closing
said compressed air injection hole.

add
B1